

Zeagle Flathead 7 Regulator

The wide-open internal structure of the Flathead 7 allows for direct and unrestricted airflow through the 1st stage, giving very low breathing resistance, even at great depths and high demands. Has a dry-sealed spring chamber (to stop freezing at water temperatures below 40 degrees F). All delicate parts of the 1st stage including the main spring are sealed behind the clear hydrostatic diaphragm away from the effects of salt or other contaminants in the water, making it environmentally sealed. Very low in profile, barely extending above the tank valve. Places low pressure hoses directly out to the sides. A conical precision, high-pressure valve provides greater reliability and service life than conventional designs.



Product Specifications

350-8110 Flathead 7 yoke / 350-8120 Flathead 7 DIN without adapter / 350-8121 Flathead LT DIN with adapter. **FIRST STAGE:** Balanced - 5 LP Ports / 2 HP Ports - Lighter weight. **SECOND STAGE:** Downstream valve - Balanced Diaphragm - Dive/Pre Dive Venturi Control - Diver Adjustable Breathing Sensitivity - New Compact Profile - Hose Length: 30 in. (.76 m).

Available at Innerspace Watersports Inc. Call Toll-Free in BC at: 1-877-549-2040 or local: Vernon Store: 250.549.2040 Kelowna Store: 250.763.2040